

LINQCELL GDP340

Graphitized Carbon Paper

• 0.34mm - 340um - 13.4mil

TP Resistance: <10 mΩcm²

Comes in Roll form

LINQCELL GDP340 is a carbon paper without a Microporous layer and without PTFE. It is commonly used as a gas diffusion layer and electrode for fuel cells. Its through plane resistivity is less than 10 m Ω cm 2 . The thickness can reach 0.18mm at 1mPa.

LINQCELL GDP340 is a close alternative to the discontinued Spectracarb 1550. This gas diffusion layer can be compressed ~50% at 100kPa. It is the only product that comes in long roll form.

Property	Value	Unit
Thickness @25kpa	0.34	mm
Thickness @1mPa	0.18	mm
Basis weight	90	g/m²
Resistance (TP)	<10	$m\Omega cm^2$
Permeability	<42	sec
Compression @90kPa	48	%

TP: Through plane

Storage and Handling

Shelf life is more than 1 year if stored in a dry and cool, well ventilated place at room temperature.

Do not leave exposed to moisture and sunlight for long periods of time. Don't throw the plate or put heavy pressure on it and the box to avoid breaking. Do not apply uneven pressure on the plate.

Europe

Industrieweg 15E, 1566JN Assendelft The Netherlands Phone: +31 (20) 893 2224 Email: info@caplinq.com

North America

957 Snowshoe Crescent Orléans ON, K1C 2Y3 Canada

Phone: +1 (613) 482-2215 Email: info@caplinq.com



United States

847 Sumpter Road #5155 Detroit, MI 48111 United states +1 (313) 558-8243 Email: info@capling.com

Asia

Minle Garden, Baoan dst Shenzhen City - 51831 China

Phone: +861368608 1428 Email: info@capling.com