LINQALLOY AuPdCu



Bonding wire

- 0.01 0.2% Gold Flash (Au)
- 1.2 2.5% Palladium Coating (Pd)
- · Copper (Cu) Balance

Linqalloy AuPdCu is a winded smooth surfaced, unpolluted bonding wire, ideal for wire bonding in IC semiconductor applications. It is available in thicknesses ranging from 18 to 25 microns and is fully compliant with the RoHS requirements of specific hazardous substance control.

They have been proven to provide better sulfidation corrosion resistance than the traditional alternatives while also improving Palladium segregation during the electric flame off process. Additionally they tend to stabilize the electrical resistivity of the bond while also requiring reduced starting voltage.

Wire types

Diameter (um)	Breaking Force (gf)	Elongation (%)	Length (m)
18	<4	5-15	500/1000
20	>5	5-15	500/1000
23	>7	7-17	500/1000
25	>9	7-17	500/1000

Chemical Composition

Chemical Element	Percentage %	CAS#	EC#
Copper (Cu)	Balance	7440-50-8	231-159-6
Gold(Au)	0.01 - 0.2	7440-57-5	231-165-9
Palladium (Pd)	1.2 - 2.5	7440-05-3	231-115-6
Other	<1000ppm	-	-

Typical Properties

Profile		Unit			
Diameter	0.7	0.8	0.9	1	mil
Fusing Current	340 - 400	420 - 480	460 - 250	490 - 550	mA
	Hv		40 - 75		FAB
Hardness	Hv		40 - 80		HAZ
	Hv		50 - 80		Wire
Density		g/cm3			
Resistivity @ RT		μΩ*cm			
CTE	16.9				ppm
Melting point		°C			

Storage and Handling

- Gold flash Palladium coated Copper wires can be stored for 6 months in a vacuum sealed bag.
- The vacuum sealed product needs to be stored in a stable and clean environment. The optimum storage temperature is ±25°C with a relative humidity ranging from 30% to 70%. Once unsealed, put the product in a Nitrogen protected environment (up to 7 days). Otherwise, the recommended service life is 50 hours for ambient exposure.

Europe

Industrieweg 15E, 1566JN Assendelft The Netherlands Phone: +31 (20) 893 22

Phone: +31 (20) 893 2224 Email: info@capling.com

North America

957 Snowshoe Crescent Orléans ON, K1C 2Y3 Canada

Phone: +1 (613) 482-2215 Email: info@capling.com



United States

847 Sumpter Road #5155 Detroit, MI 48111 United states +1 (313) 558-8243 Email: info@capling.com

Asia

Minle Garden, Baoan dst Shenzhen City - 51831 China

Phone: +861368608 1428 Email: info@capling.com