

# LINQCELL CF350

## Carbon cloth

- 0.35mm - 350um - 14mil
- Comes in roll form
- >5 mΩcm<sup>2</sup> TP Resistance

**LINQCELL CF350** is a 0.35mm thick carbon cloth without a Microporous layer and PTFE. It is commonly used as a gas diffusion layer and electrode for fuel cells. Its through-plane resistivity is less than 5 mΩcm<sup>2</sup>.

**LINQCELL CF350** carbon cloth is typically used in PEM, Phosphoric acid and Direct methanol fuel cell applications as a gas diffusion layer. Carbon cloth based GDLs have performance equal to that of conventional carbon papers. Carbon cloth is more practical than carbon paper because of its superior compressibility, elasticity, and flexibility performance, making it more appropriate for ongoing manufacturing and assembly processes.

Property	Value	Unit
Thickness	0.35	mm
Tensile strength (MD/XD)	10/5.5	N/cm
Basis weight	132	g/m <sup>2</sup>
Resistance (TP)	<5	mΩcm <sup>2</sup>
Permeability (Air)	<9.5	sec
MPL + PTFE	Yes	-

TP: Through plane

### Storage and Handling

Shelf life is more than 2 years if stored in a dry and cool, well ventilated place at room temperature.

Do not leave exposed to moisture and sunlight for long periods of time.

#### Europe

Industrieweg 15E,  
1566JN Assendelft  
The Netherlands  
Phone: +31 (20) 893 2224  
Email: info@caplinq.com

#### North America

957 Snowshoe Crescent  
Orléans ON, K1C 2Y3  
Canada  
Phone: +1 (613) 482-2215  
Email: info@caplinq.com



#### United States

847 Sumpter Road #5155  
Detroit, MI 48111  
United states  
+1 (313) 558-8243  
Email: info@caplinq.com

#### Asia

Minle Garden, Baoan dst  
Shenzhen City - 51831  
China  
Phone: +861368608 1428  
Email: info@caplinq.com