

LINQTAPE PET1S-Blue-DCD



1-mil Blue Polyester Tape with Silicone Adhesive

- 1 mil die cut polyimide film
- Silicone adhesive
- 4200V breakdown voltage

LINQTAPE™ PET1S-Blue-DCD is a 1-mil polyester film backing with a pressure sensitive silicone adhesive system. The low residue PSA Silicone adhesive is designed for splicing and masking applications where high initial adhesion is required, but no residues should remain once the tape is removed.

LINQTAPE™ PET1S-Blue-DCD films come in varying designs and patterns. They are available in a range of thicknesses, starting from 0.5 mil (12.7µm) thickness and up. This film can be delivered in a range of die cut discs sizes with diameters ranging from 1/8" to 12". Custom thicknesses, designs and diameters are available upon request.

Specifications

Property	Value	Unit
Color	Blue	-
Adhesive Type	Silicone	-
Film Thickness	25.4 (1)	um (mil)
Adhesive Thickness	43.2 (1.7)	um (mil)
Release liner	None	-
Total Thickness	68.6 (2.7)	um (mil)
Temperature Resistance	200	°C
Tensile Strength	25	lbs/in
Elongation	>100	%
Breakdown Voltage	4200	Volts
Peel Strength	30	oz/in
Insulation Class	180°	(H)

Storage and Handling

Shelf life is 2 years if stored in a dry, cool and well ventilated place at room temperature.

The product is supplied in rolls and should be kept in a cool (10°C – 25°C) dry place (40% – 75% humidity) away from direct sunlight or temperature extremes. Once removed from packaging it should be protected against dust and other impurities.

Europe

Industrieweg 15E,
1566JN Assendelft
The Netherlands
Phone: +31 (20) 893 2224
Email: info@caplinq.com

Canada

80 Sirocco Crescent
Ottawa ON, K2S 2C9
Canada
Phone: +1 (613) 482-2215
Email: info@caplinq.com



North America

36927 Schoolcraft Rd
Livonia, MI 48150
United States
Phone: +1 (313) 558-8243
Email: info@caplinq.com

South East Asia

S-08-07 Persiaran Triangle
B Lepas, Penang 11900
Malaysia
Phone: +60 (12) 4302223
Email: info@caplinq.com