

# OCA - Optically Clear Adhesive

## Antistatic PET Film with Optically Clear Adhesive

- >92% Light Transmittance
- <0.5% Haze
- 0.1 mm

OCA is an optical anti-glare film with antistatic properties. It is made out of polyester film, with an optically clear acrylic adhesive and release liner. The adhesive is made out of double-layer explosion-proof film, which is specifically designed for the protection of the substrate.

OCA is an extremely thin material with a total thickness of 0.06 mm. With a light transmittance of >92% and Haze of <0.5% it is a great material for where optical clearance is required. The material has a stable viscosity, and good weather resistance, and does not experience any yellowing or discoloration.

### Specifications

Property	Value	Unit
Color	Transparent	-
Adhesive Type	Acrylic	-
Film Thickness	0.050 (1.96)	mm (mil)
Adhesive Thickness	0.01 (0.39)	mm (mil)
Release Liner Thickness	0.050 (1.96)	mm (mil)
Total Thickness	0.06 (2.36)	mm (mil)
Peel Force (g/25mm)	1628.34	g
Light Transmittance	>92	%
Haze	<0.5	%
ROHS	Pass	
Operating Temperature	-40 ~ 110	°C

### Storage and Handling

Shelf life is 2 years if stored in a dry and cool, well ventilated place at room temperature.

The product is supplied in rolls and should be kept in a cool (10°C – 25°C) dry place (<65% humidity) away from direct sunlight or temperature extremes. Once removed from packaging it should be protected against dust and other impurities.

#### Europe

Industrieweg 15E,  
1566JN Assendelft  
The Netherlands  
Phone: +31 (20) 893 2224  
Email: info@caplinq.com

#### Canada

80 Sirocco Crescent  
Ottawa ON, K2S 2C9  
Canada  
Phone: +1 (613) 482-2215  
Email: info@caplinq.com



#### North America

36927 Schoolcraft Rd  
Livonia, MI 48150  
United States  
Phone: +1 (313) 558-8243  
Email: info@caplinq.com

#### South East Asia

S-08-07 Persiaran Triangle  
B Lepas, Penang 11900  
Malaysia  
Phone: +60 (12) 4302223  
Email: info@caplinq.com