

LINQTAPE PIT3S-T-RL



3 mil polyimide film with thin silicone adhesive and release liner

- 3 mil polyimide film
- 1mil silicone adhesive
- 15,000V breakdown voltage

LINQTAPE™ PIT3S-T-RL is an amber high-temperature resistant polyimide film designed for both permanent and temporary bonding in many high temperature applications. These applications can be found in semiconductor, smartcard, electronic, automotive and general manufacturing industries. It is ideal for applications that require the balancing of multiple properties over a wide temperature range.

LINQTAPE™ PIT3S-T-RL Film comes in 33 meter (36 yard) rolls of varying widths. LINQTAPE PIT-S polyimide films with silicone adhesive are available in a range of thicknesses, starting from 0.5 mil (12.7µm) thickness and up. Custom thicknesses are available upon request.

Specifications

Property	Value	Unit
Color	Amber	-
Adhesive Type	Silicone	-
Film Thickness	76.2 (3)	um (mil)
Adhesive Thickness	25.4 (1)	um (mil)
Release liner	Yes	-
Total Thickness	101.6 (4)	um (mil)
Temperature Resistance	260	°C
Tensile Strength	80	lbs/in
Elongation	60	%
Breakdown Voltage	15,000	Volts
Adhesion to Steel	12.5	oz/in

Storage and Handling

Shelf life is 2 years if stored in a dry and cool, well ventilated place at room temperature.

The product is supplied in rolls and should be kept in a cool (10°C – 25°C) dry place (40% – 75% humidity) away from direct sunlight or temperature extremes. Once removed from packaging it should be protected against dust and other impurities.

Europe

Industrieweg 15E,
1566JN Assendelft
The Netherlands
Phone: +31 (20) 893 2224
Email: info@caplinq.com

Canada

80 Sirocco Crescent
Ottawa ON, K2S 2C9
Canada
Phone: +1 (613) 482-2215
Email: info@caplinq.com



North America

36927 Schoolcraft Rd
Livonia, MI 48150
United States
Phone: +1 (313) 558-8243
Email: info@caplinq.com

South East Asia

S-08-07 Persiaran Triangle
B Lepas, Penang 11900
Malaysia
Phone: +60 (12) 4302223
Email: info@caplinq.com