

## SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name LINQBOND™ PM-1231

Applications: Transparent two-part epoxy resin for casting bonding, potting, and sealing electronic

components

Advised Against No further relevant information available

Supplier Name Capling Europe BV

CAPLINQ Europe BV Industrieweg 15E 1566 JN Assendelft The Netherlands

+31 20 893 2224

CAPLINQ Corporation 80 Sirocco Crescent Ottawa, ON K2S 2C9 Canada CAPLINQ Americas 36972 Schoolcraft Rd Livonia, MI 48150 United States of America CAPLINQ Malaysia S-08-07 Setia Triangle Penang, BL 11900

Malaysia

+1 (613) 416 8426

+1 (618) 416 9739 +60 (15) 460 00453

## SECTION 2. HAZARDS IDENTIFICATION

## **CLASSIFICATION**

Skin SensitizationCategory 1Skin Corrosion/IrritationCategory 1BSerious Eye Damage/IrritationCategory 1Specific Target Organ ToxicityCategory 3

(Single Exposure; Respiratory Tract Irritation)

Specific Target Organ Toxicity Category 2

(Repeated Exposure)

Acute Oral Toxicity Category 4
Hazardous to the Aquatic Environment Category 1

(Acute Hazard)

Hazardous to the Aquatic Environment Category 2

(Long-term Hazard)

## **SIGNAL WORD**

Warning

#### **HAZARD PICTOGRAM**





#### **HAZARD STATEMENTS**

H302 Harmful if swallowed

H314 Causes severe skin burns and eye damage
 H317 May cause an allergic skin reaction
 H335 May cause respiratory irritation
 H400 Very toxic to aquatic life

H411 Toxic to aquatic life with long lasting effects

#### **PRECAUTIONARY STATEMENTS**

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.



#### **RESPONSE PRECAUTIONARY STATEMENTS**

P302+P351 IF ON SKIN: Rinse cautiously with water for several minutes.

P305+P316+P338 IF IN EYES: Get emergency medical help immediately. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment: Refer to detailed instructions provided on this SDS

## **SECTION 3. INGREDIENT COMPOSITION**

#### Part A

No.	Components	CAS Reg. No.	Proportion (%)
1	Epoxy resin	38891-59-7	30-90
2	Benzyl glycidyl ether	2930-05-4	10-20
3	Aluminum hydroxide	21645-51-2	0-25
4	Alumina	1344-28-1	0-20
5	Pigment	_	0-5

#### Part B

No.	Components	CAS Reg. No.	Proportion (%)
1	Phenol	90-72-2	10-30
2	Aromatic amine	593-00-0	30-50
4	Polythiol	31775-89-0	0-30

#### **SECTION 4. FIRST AID MEASURES**

## **EYE CONTACT**

• Immediately flush with plenty of water for at least 10 min.

## **SKIN CONTACT**

No first aid required.

#### INHALATION

- Move victim to fresh air.
- Administer oxygen if breathing is difficult.
- If symptoms persist, seek medical attention.

#### **INGESTION**

- Do not administer anything orally if the patient is on the verge of losing consciousness, already unconscious, or experiencing convulsions.
- Do not induce vomiting.
- · Get medical attention immediately.

## **SECTION 5. FIRE FIGHTING MEASURES**

## **EXTINGUISHING MEDIA**

Dry chemicals, water mist, or foam.

# A CAPLING

# Safety Data Sheet

#### SPECIAL FIREFIGHTING PROCEDURES AND EQUIPMENT

- · Wear self-contained breathing apparatus and protective clothing.
- According to the local emergency plan, decide whether evacuation or isolation of the area is necessary.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

PERSONAL PROTECTION PRECAUTION: Avoid eye contact. Keep the container sealed. Do not ingest.

#### LEAK/SPILL

- In case of a leakage, use sand, soil, or other appropriate materials to contain and prevent environmental contamination.
- Report as per regulatory requirements. Refer to the local emergency plan to determine whether evacuation or
  area isolation is necessary. Promptly transfer leaked material into a suitable container and utilize appropriate
  absorbents to clean up any remaining spills.

## **SECTION 7. HANDLING AND STORAGE**

#### **HANDLING**

- Ensure the availability of suitable protective and ventilation equipment.
- Minimize skin and eye exposure, and prevent inhalation of vapors. Do not stay in contact for an extended period.

#### **STORAGE**

• Store in a cool and dry place away from excessive heat, sunlight, and humidity. Exercise caution and store separately from oxidizing materials.

## SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### **EXPOSURE LIMITS**

No.	Components	Standards*	Reference
1	Epoxy resin	Not Established	OSHA <sup>1</sup> /ACGIH <sup>2</sup>
2	Benzyl glycidyl ether	Not Established	OSHA <sup>1</sup> /ACGIH <sup>2</sup>
3	Aluminum hydroxide	Not Established	OSHA <sup>1</sup> /ACGIH <sup>2</sup>
4	Alumina	Not Established	OSHA <sup>1</sup> /ACGIH <sup>2</sup>
5	Phenol	Not Established	OSHA <sup>1</sup> /ACGIH <sup>2</sup>
6	Aromatic amine	Not Established	OSHA <sup>1</sup> /ACGIH <sup>2</sup>
7	Polythiol	Not Established	OSHA <sup>1</sup> /ACGIH <sup>2</sup>

<sup>&</sup>lt;sup>1</sup>Occupational Safety and Health Administration (OSHA) 8-hour total weight average (TWA) permissible exposure limit (PEL)

#### **VENTILATION**

Use general or local exhaust ventilation to meet exposure limit requirements.

#### PERSONAL PROTECTION

- Respiratory Protection: No special protective equipment is necessary when operating in areas equipped with ventilation and exhaust facilities.
- Eye/Skin Protection: Chemical safety splash goggles, and eyewash equipment are recommended. Do not wear contact lenses.

<sup>&</sup>lt;sup>2</sup>American Conference of Governmental Industrial Hygienists (ACGIH) 8-hour total weight average (TWA) threshold limit value (TLV)



## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Grayish viscous liquid (Part A)

Light yellow viscous liquid (Part B)

OdorMild odorpHNot availableInitial Boiling Point/Boiling RangesNot availableFlash PointNot available

Viscosity 6000-9000 cP (Part A)/ 300-400 cP(Part B)

Vapour Pressure (mmHg at 25 °C)

Evaporation Rate (Butyl Acetate = 1)

Not available

Not applicable

#### SECTION 10. STABILITY & REACTIVITY

Chemical Stability: Stable under ordinary conditions of use and storage.

Decomposition Products: Ethanol, carbon dioxide, and trace amounts of unburned carbides.

**Hazardous Polymerization:** No hazard at room temperature.

#### SECTION 11. TOXICOLOGICAL INFORMATION

Carcinogenicity: No information found Reproductive Effect: No information found Chronic Effects: No information found Target Organs: No information found Eye Contact: May cause mild eye irritation.

Ingestion: May be hazardous to the digestive system, cause vomiting and loss of appetite.

Inhalation: May cause respiratory tract irritation, vomiting, and loss of appetite.

**Skin Contact:** May cause mild skin inflammation.

#### SECTION 12. ECOLOGICAL INFORMATION

**Mobility:** No Information found

**Bioaccumulation:** No information found **Biodegradability:** No information found **Aquatic Toxicity:** No information found

**Environmental Toxicity:** No information found

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal of waste needs to be carried out at the city, state, or federally permitted disposal facility. Handle in accordance with applicable regulations and/or local authorities.

## **SECTION 14. TRANSPORT INFORMATION**

This product is not classified as dangerous goods according to international transport regulations.

Version No: 02

Land transport ADR/RID (Cross-border)

ADR, RID Class:

Not subject to ADR classification.

Maritime transport IMDG IMDG Class:

Not subject to IMDG classification.

Air transport ICAO-TI and IATA-DGR

Printing date: 04.07.2024

SDS LINQBOND™ PM-1231 | Page 4 of 4



Not subject to IATA classification.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized safety officer. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

## **SECTION 15. REGULATORY INFORMATION**

No information available

## **SECTION 16. OTHER INFORMATION**

The information in this safety data sheet was obtained from reputable sources and to the best of our knowledge is accurate and current at the mentioned date. Neither CAPLINQ Corporation, nor CAPLINQ Europe BV accept any liability arising out of the use of the information provided here or the use, application or processing of the product described herein.

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgments of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Version No: 02

Printing date: 04.07.2024