

PRODUCT DESCRIPTION**Technology**

Hot Melt

Product Type

Cleaning agent

Application

Graphic Industry

Appearance

Blue

Application Areas

Cleaning Agent for Polyurethane Hotmelts

Product Properties

TECHNOMELT PUR CLEANER 2 is used for cleaning of application equipment, melting systems and such like which are used for polyurethane hotmelt adhesives applications. TECHNOMELT PUR CLEANER 2 converts the reactive components of the poly-urethane hotmelt adhesive, to rule out further crosslinking processes.

Technical Data*Viscosity, Brookfield* - 130 °C, 5,500 to 7,500*Density, g/cm³* 0.9 to 1.0*Softening Point, Ring & Ball, °C* 68 to 76**DIRECTIONS OF USE**

Prior to application it is necessary to read the Material Safety Data Sheet for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Processing

At application processes with melt pot granulated TECHNOMELT PUR CLEANER 2 is used.

At working with drum melt units TECHNOMELT PUR CLEANER 2 is available in equivalent hobbocks or drums.

TECHNOMELT PUR CLEANER 2 is bluish colored to facilitate the cleaning process.

Working Temperature

Commonly TECHNOMELT PUR CLEANER 2 is used with the same application temperature as the polyurethane hotmelt which was applied during the working process (90 to 140) °C.

STORAGE

Rotate stock, using oldest material first. Keep containers upright and closed to prevent contamination. Do not mix with other adhesives. When stored in a dry and cool place in the original unopened containers shelf life is as follows.

Shelf life

Shelf-life (in unopened original packaging), 24 months
Frost-Sensitive: No

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all marks used are trademarks of Henkel or its affiliates in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Henkel Corporation

Tel: 1.888.480.6889

Email: bw.nacustomerservice@henkel.com

www.henkelna.com

